



■ SPECIFICATIONS

- Voltage Rating : 50V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ WAFER

- Poles : 2~13(Right Angle)
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-0 + Glass Fiber
- Q' ty : 1,000pcs./Bag

Circuit	KInK					
	Circuit No.					
	1	2	3	4	5	6~13
2	KInK	KInK				
3	KInK		KInK			
4	KInK			KInK		
5~13	N	KInK			KInK	N

Poles	Dimensions(mm)		
	A	B	C
2	1.50	4.50	3.60
3	3.00	6.00	5.10
4	4.50	7.50	6.60
5	6.00	9.00	8.10
6	7.50	10.50	9.60
7	9.00	12.00	11.10
8	10.50	13.50	12.60
9	12.00	15.00	14.10
10	13.50	16.50	15.60
11	15.00	18.00	17.10
12	16.50	19.50	18.60
13	18.00	21.00	20.10

<p>RoHS Compliant</p>		<p>HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.</p>	
<p>APPD. 核准 Hedy</p>	<p>DWG. 製圖 Helen</p>	<p>DATE 制表日 2010/05/11</p>	<p>PART NAME 品名 1.50mm WAFER 1X??P RIGHT ANGLE TYPE TIN PLATING BAG PACKING IVORY COLOR ROHS</p>
<p>SCALE 比例 參考</p>	<p>UNIT 單位 MM</p>	<p>PAGE 張數 1 / 1</p>	<p>PART NO. 料號 W1600-XXPRTBIOR</p>
<p>TOLERANCE 容許公差 .0 ±0.3 .00 ±0.2 ALL ±</p>	<p>SIZE 紙張尺寸 A 4</p>	<p>REV. 版次 A</p>	