



RECOMMENDED P.C.BOARD LAYOUT DIMM.

Specifications

- Current Rating: 3A AC/ DC (Max)AWG#22
- Voltage Rating: 250V AC/ DC
- Temperature Range: -25°C ~ + 85°C
- Contact Resistance: 20mΩ Max
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage:800V AC/Minute
- Pin : Brass/ Tin-plated/ Gold-flash
- Wafer Material: Nylon 6T,UL94V-0,natural
- Solder tab:Brass/Tin-plated

Poles	Dimension mm (in.)	
	A	B
10	18.0(0.709)	24.0(0.945)
11	20.0(0.787)	26.0(1.024)
12	22.0(0.866)	28.0(1.102)
13	24.0(0.945)	30.0(1.181)
14	26.0(1.024)	32.0(1.260)
15	28.0(1.102)	34.0(1.338)

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 DWG. 製圖 <i>Helen</i> DATE 創表日 2013/6/10	 TOLERANCE 容許公差 .0 ± 0.25 .00 ± 0.2 ANG. ± SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	PART NAME 品名 JST PA 2.0mm WAFER 1X(10~15)P SMT RIGHT ANGLE TYPE TIN PLATING WHITE INSULATOR ROHS PART NO. 料號 W2112-(10~15)PBTWX0R	SIZE 紙張尺寸 A4 REV. 版本 A