



Specifications

Current Rating: 3A AC/ DC (Max)AWG#22
 Voltage Rating: 250V AC/ DC
 Temperature Range: -25°C ~ + 85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage:800V AC/Minute
 Pin : Brass/ Tin-plated/ Gold-flash
 Wafer Material: Nylon 6T,UL94V-0,natural
 Solder tab:Brass/Tin-plated

Poles	Dimension mm (in.)	
	A	B
10	18.0(0.709)	24.0(0.945)
11	20.0(0.787)	26.0(1.024)
12	22.0(0.866)	28.0(1.102)
13	24.0(0.945)	30.0(1.181)
14	26.0(1.024)	32.0(1.260)
15	28.0(1.102)	34.0(1.338)

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 BETTY	SCALE 比例 参考	TOLERANCE 容許公差 X.XX ± 0.20 X.X ± 0.25
DWG. 製圖 BETTY	UNIT 單位 MM	SIZE 紙張尺寸 A 4
DATE 制表日 2010/01/08	PAGE 張數 1 OF 1	REV. 版次 A
PART NAME 品名 JST PA 2.0mm WAFER 1XXXP SMT STRAIGHT TYPE TIN PLATING WHITE INSULATOR		PART NO. 料號 W2112-XXPATWX0R