



### SPECIFICATIONS

Electrical  
 Current Rating: 5A AC, DC  
 Voltage Rating: 250V AC, DC  
 Operating Temp.: -25°C ~ +85°C  
 Insulation Resistance: 1000MΩ/ min.  
 Dielectric Withstanding Voltage: 1500V AC/ min.  
 Contact Resistance: 10mΩ/ max.

Poles	A	B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.80
6	19.80	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.60
11	39.60	43.56
12	43.56	47.52

### ORDER INFORMATION

Contact No.  02-20  
 Contact Type  P: Non Distribution  
 Function  S: Straight  
 Body Option  Y: W/ Back (2-20)  
 Contact Plating  T: Tin  
 Insulator Color  W: White  
 0: Fill It With "0"  
 R: ROHS LOW LEAD  
 N: W/O Back (2-12)  
 S: Selective Gold  
 G: Gold Flash

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 DATE 2018/01/08	SCALE 比例 參考 UNIT 單位 M M PAGE 張數 1 OF 1	TOLERANCE 容許公差 .0 ± 0.5 .00 ± 0.35 ANG. ± SIZE. 紙張尺寸 A 4 REV. 版次 B	PART NAME 品名 MX3.96 WAFER 180° ROUND PIN PART NO. 料號 W2401-XXPSXXW0R