



SPECIFICATIONS
 Current Rating: 7A AC,DC
 Voltage Rating: 600V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 3mΩ Max.
 Insulation Resistance: 5000MΩ Min.
 Withstanding Voltage: 2200V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

Circuit No.	Dimensions		Circuit No.	Dimensions	
	A	B		A	B
02P	3.96	7.92	12P	43.56	47.52
03P	7.92	11.88	13P	47.52	51.48
04P	11.88	15.84	14P	51.48	55.44
05P	15.84	19.80	15P	55.44	59.40
06P	19.80	23.76	16P	59.40	63.36
07P	23.76	27.72	17P	63.36	67.32
08P	27.72	31.68	18P	67.32	71.28
09P	31.68	35.64	19P	71.28	75.24
10P	35.64	39.60	20P	75.24	79.20
11P	39.60	43.56			

APPD. 核准 HELEN DWG. 製圖 ABBY DATE 制表日 2012/01/06		SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1		TOLERANCE 容許公差 X.X±0.25 X.XX±0.15 X.XXX±0.05		PART NAME 品名 3.96mm WAFER RIGHT ANGLE TYPE 1XXXP SQUARE PIN DIP L=3.18mm WITH LOCKING RIBS (L=10.8mm) TIN PLATED WHITE COLOR ROHS	
RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.		PART NO. 料號 W2402-XXPRYTW0R			