



SPECIFICATIONS

Electrical

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC/ max.
 Operating Temp.: -25°C ~ +85°C
 Insulation Resistance: 1000MΩ/ min.
 Dielectric Withstanding Voltage: 800V AC/ min.
 Contact Resistance: 10mΩ/ max.

Material

Terminal Material: Brass, Copper-Undercoated,/
 Tin-Lead plated
 Material: Nylon 66, UL94V-0

Poles	Dimension mm (in.)	
	A	B
2	2.50 (0.098)	7.50 (0.295)
3	5.00 (0.197)	10.00 (0.394)
4	7.50 (0.295)	12.50 (0.492)
5	10.00 (0.394)	15.00 (0.591)
6	12.50 (0.492)	17.50 (0.689)
7	15.00 (0.591)	20.00 (0.787)
8	17.50 (0.689)	22.50 (0.886)
9	20.00 (0.787)	25.00 (0.984)
10	22.50 (0.886)	27.50 (1.082)
11	25.00 (0.984)	30.00 (1.181)
12	27.50 (1.082)	32.50 (1.280)

RoHS Compliant	HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
	APPD. 核准 DWG. 製圖 <i>Helen</i> DATE 制表日 2020/11/17	TOLERANCE 容許公差 0 ± 0.35 .00 ± 0.25 ANG. ± 3° SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1