



**Features:**

- 4 ~ 24 circuits available
- Plastic material: LCP
- Pin material: Brass
- .0246"(0.625mm) square pin && N = 4 ~ 24
- Recommended PCB thickness: .062"(1.57mm)

**Dimensional Information ( mm )**

Circuits	N
Dim. A	3 x ( N / 2 - 1 )
Dim. B	A + 10
Dim. C	A - 4.32

**Specification:**

- Voltage rating: 250V AC(RMS) or DC
- Current rating: 5A AC, DC
- Contact resistance: 10mΩ Max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

PCB Layout: Component side

RoHS Compliant		 <b>玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准	SCALE 比例 参考	UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.05 ( mm ) .00 ± 0.15 ( mm ) .0 ± 0.25 ( mm )	PART NAME 品名 Micro-Fit 3.0mm BMI Type 2XXXP RIGHT ANGLE TYPE WITH RETENTION PEG WITHOUT BRACKET TIN PLATING BLACK COLOR MATERIAL: LCP ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE 紙張尺寸 A 4	PART NO.
DATE 制表日 2017/05/26	PAGE 張數 1 OF 1	REV. 版次 B	料號 W4231-XXPRATB0R