



PCB Layout: Component side

Recommended PCB thickness: .062"(1.57mm)

Features:

- 4 ~ 24 circuits available
- Plastic Material: LCP
- ⚠ • Tin-plated brass
- ⚠ • .0246"(0.625mm) square pin

Specification:

- Voltage rating: 250V AC(RMS) or DC
- Current rating: 5A AC, DC
- Contact resistance: 10mΩ Max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -40°C ~ 105°C

Dimensional Information (mm)

Circuits	N
Dim. A	$3 \times (N / 2 - 1)$
Dim. B	$3 \times (N / 2) + 7$

&& N = 4 ~ 24

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 參考	UNLESS OTHERWISE SPECIFIED TOLERANCE .000 ± 0.05 (mm) .00 ± 0.15 (mm) .0 ± 0.25 (mm)	PART NAME 品名 Micro-Fit 3.0mm BMI Type 2XXXP STRAIGHT TYPE WITH RETENTION PEG WITHOUT BRACKET TIN PLATING BLACK COLOR MATERIAL:LCP ROHS
DWG. 製圖 Betty	UNIT 單位 M M	SIZE. 紙張尺寸 A 4	PART NO. 料號 W4231-XXPSATB0R
DATE 制表日 2013/11/27	PAGE 張數 1 OF 1	REV. 版次 A	