



**Specifications**

Electrical  
 Voltage Rating: 30V(AC, DC)  
 Current Rating: 0.3A AC/ DC(AWG#34)  
                   0.2A AC/ DC(AWG#36)  
 Withstanding Voltage: 200V AC/ minute  
 Insulation Resistance: 100MΩ Min  
 Contact Resistance: 40mΩ Max

**NOTE :**

**MATERIAL:**  
 Housing: LCP, UL 94V-0  
 Terminal: Phosphor bronze t=0.12mm  
 Fitting: Brass t=0.15mm  
 Plating: Gold plated  
 Circuits: 4, 5, 6, 8, 10, 12  
 Temperature Range: -25°~+85°C

CIRCUITS	DIMENSION		
	A	B	C
4	4.20	2.56	1.80
5	4.80	3.16	2.40
6	5.40	3.76	3.00
8	6.60	4.96	4.20
10	7.80	6.16	5.40
12	9.00	7.36	6.60

APPD. 核准 Betty DWG. 製圖 Helen DATE 制表日 2020/7/27		RoHS Compliant HSM 玄茂科技股份有限公司 HSIUAN MAO TECHNOLOGY CO., LTD.	TOLERANCES UNLESS NOTED LINEAR ± x ±0.3 xx ±0.15 xxx ±0.08 ANGLES ± ? SIZE: 紙張尺寸 A 4 REV. 版次 B	PART NAME 品名 JST XSR 0.6mm WAFER SMT RIGHT ANGLE TYPE 1XXXP GOLD FLASH PLATING MATERIAL:LCP UL94V-0 BLACK COLOR ROHS PART NO. 料號 W6110-XXPBGBX0R
UNIT 單位 M M PAGE 張數 1 OF 1				