



Specification:

1、Material: Rubber shell:PA66 UL94V-2 PIN:H65(Plating:SnSb)

Material:Phosphor Bronze (QSn6.5-0.1/C5191)

- 2、Current rating: 20A max
- 3、Voltage rating: 300V AC/DC
- 4、Temperature range:-25°Cto+85°C
- 5、Contact resistance: $\leq 10m\Omega$
- 6、Insulation resistance: $\geq 1000M\Omega$
- 7、Withstand voltage:2000V AC/minute
- 8、Fixing force of pins: $\geq 25N$
- 9、Applicable PC board thickness:1.6mm

RoHS Compliant		HSM 玄茂科技股份有限公司										
		HSUAN MAO TECHNOLOGY CO., LTD.										
APPD. 核准	HELEN		TOLERANCE									
DWG. 製圖	ABBY		<table border="1"> <tr><td>≤ 3</td><td>± 0.1</td></tr> <tr><td>≤ 10</td><td>± 0.2</td></tr> <tr><td>≤ 20</td><td>± 0.3</td></tr> <tr><td>≤ 40</td><td>± 0.4</td></tr> <tr><td>≤ 80</td><td>± 0.5</td></tr> </table>	≤ 3	± 0.1	≤ 10	± 0.2	≤ 20	± 0.3	≤ 40	± 0.4	≤ 80
≤ 3	± 0.1											
≤ 10	± 0.2											
≤ 20	± 0.3											
≤ 40	± 0.4											
≤ 80	± 0.5											
DATE 制表日	2022/02/18	UNIT 單位	MM									
		PAGE 張數	1 OF 1									
		REV. 版次	A									
		PART NAME 品名										
		6.2MM WAFER STRAIGHT TYPE SINGLE ROW										
		1X3PIN W/ LOCKING RIBS TIN PLATING										
		WHITE COLOR NY66 UL94V-2 BAG PACKING ROHS										
		PART NO.										
		料號 W6211-03PSSTW0GR										