



**Material & finish**

**SHELL:**

Steel  
Zinc plated, Tin plated  
or Nickel plated steel

**PIN CONTACT:**

Phosphor bronze or brass  
Gold plated

**INSULATOR:**

PBT & Glass-fibre reinforced  
UL-94-V0

**CURRENT RATING:**

5 Amp

**DIELECTRIC STRENGTH:**

1000V for one minute

**INSULATOR RESISTANCE:**

1000MΩ Min. (at 500V DC)

Dimensinal

Circuits	A	B	C
36	67.7mm	59.7mm	90.1mm
50	82.8mm	74.9mm	103.7mm

RoHS  
Compliant

**HSM** 玄茂科技股份有限公司  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD.  
核准  
Betty

DWG.  
製圖  
Betty

DATE 制表日  
2012/08/10

SCALE  
比例 參考

UNIT  
單位 MM

PAGE  
張數 1 OF 1

SELECT  
CHECK  
1 2 3 EXTRA  
0.000 0.05 0.05 0.10  
0.05 0.10 0.15 0.20  
0.1 0.15 0.20 0.30  
0 0.25 0.30 0.40  
ANGLE 1.0° 3.0° 5.0°

SIZE  
紙張尺寸 A 4

REV.  
版次 B

PART NAME 品名  
CENTRONIC COMMUNICATION TYPE XXP  
MALE BLACK PLASTIC COVER  
SELECTIVE GOLD BLUE INSULATOR ROHS

PART NO.  
料號 C0715-XXMPSL00R

